





** Zest. dla jednego el. wysylkowego-

Nr.	Tnr	Poz.	Nazwa	Sztuk	Profil	Materiał	Długość	Waga	Ozn.
1	2	33	Dźwigar	1	IPE220	S235JR	10570	276.92	
2	2	1181	Kątownik	1	BLL 120*80*3	S235JR	4899	22.73	
3	2	1185	Kątownik	1	BLL 120*80*3	S235JR	3463	16.07	
4	2	1187	Kątownik	1	BLL 120*80*3	S235JR	1221	5.66	
5	2	1229	Blacha	1	PL12*180	S235JR	249	4.22	
6	2	1230	Blacha	1	PL12*178	S235JR	251	4.21	
7	2	1234	Blacha	1	PL12*166	S235JR	223	3.50	
8	2	1240	Blacha	2	PL14*140	S235JR	240	7.39	
9	2	1252	Blacha	2	PL16*100	S235JR	150	3.77	
10	2	1259	Blacha	2	PL12*80	S235JR	200	3.01	
11	2	1268	Blacha	2	PL8*52	S235JR	200	1.30	
Waga całkowita (kg)								348.77	
Gabaryty (W x S x D): 380 x 333 x 10598									



** Zest. dla jednego el. wysylkowego-

Nr.	Tnr	Poz.	Nazwa	Sztuk	Profil	Materiał	Długość	Waga	Ozn.
1	2	35	Dźwigar	1	IPE220	S235JR	6085	159.42	
2	2	1180	Kątownik	1	BLL 120*80*3	S235JR	5482	25.43	
3	2	1239	Blacha	1	PL18*150	S235JR	240	5.09	
4	2	1240	Blacha	1	PL14*140	S235JR	240	3.69	
5	2	1269	Blacha	1	PL6*50	S235JR	70	0.16	
Waga całkowita (kg)								193.80	
Gabaryty (W x S x D): 280 x 225 x 6117									

